

UX 180

UX Range: 2 GHz - 6 GHz / 180 W CW



Prana UX 180

- Class A solid state
- Broadband (instantaneous single band): 2 GHz – 6 GHz
- Typical output power : 180 W CW
- Linear output power (1 dB compression) guaranteed with harmonics <-20 dBc:
 - P1dB > 100 W and H < -20 dBc up to 4 GHz and
 - P1dB > 80 W and H < -20 dBc from 4 GHz to 6 GHz
- Air cooling: self contained fans
- Can operate in full mismatch conditions without damage
- Reliable, efficient and robust
- 19" cabinet on wheels
- 3 years standard warranty

Maintenance

- Amplifier designed for minimal maintenance
 - Easy access to all parts
 - Modular design
 - Repairs with minimum adjustments
- Rapid diagnostic
- Minimal downtime
- Contract for preventive and corrective maintenance available

Applications

- EMC tests
- RF tests and instrumentation
- Radiocommunication
- Measurement and research laboratories

Versions


- UX 180 D amplifier with:
 - Display
 - Digital control
 - IEEE 488 GPIB Communication
- UX 180 DC : UX 180 D with :
 - Integrated bidirectional coupler
 - display of instantaneous power

UX Range

- UX 15 => 15 W CW
- UX 30 => 30 W CW
- UX 55 => 55 W CW
- UX 100 => 100 W CW
- UX 180 => 180 W CW

Extra

- External coupler
- Supply and integration inside a cabinet
- RF Power cable
- Switching unit



Specifications

Frequency bandwidth	2 GHz - 6 GHz
Typical output power	180 W
Power at 3 dB compression	140 W min. up to 4 GHz / 120 W min. from 4 GHz to 6 GHz *
Power at 1 dB compression	100 W min. up to 4 GHz / 80 W min. from 4 GHz to 6 GHz *
Harmonics distortion	H2,H3 < -20 dBc for the output power at 1 dB compression limit
Class type	Class A
Gain	59 dB
Linear power gain flatness	± 5 dB max
Mismatch tolerance	infinite without damage
Input impedance	50 ohms / VSWR: 2:1 max
Output impedance	50 ohms / VSWR: 2:1 max
Input power	+10 dBm max.
RF input connector	Type N fem. (front or rear panel) – other connector type on request
RF output connector	Type N fem. (front or rear panel) – other connector type on request
Safety interlock	Connector type BNC
Digital control	Transistors, power supplies and internal temperature
Communication interface	IEEE 488
4 lines digital display	Status, faults, (direct and reverse instantaneous power for DC version)
Ambient operating temperature	0 °C / + 35 °C
Room temperature storage	-20 °C / +70 °C
Cooling	Forced air: 240 l/sec max. (self contained fans)
Power voltage	200-250 VAC, 47-63 Hz, single phase
Rated current	10 A at 230 VAC
Dimensions	600 x 840 x 1050 mm (18U) / 23.6 x 33.1 x 41.3 in (18U)
Weight	230 kg / 506 lb

UX 180 DC version :

Integrated bidirectional power coupler	Coupling factor 49 dB typ.
Power coupling connector	Type N fem. (rear panel)
Estimated output power losses due to the coupler	0.5 dB * => take account these power losses for the min output power