

Prana GN 500:

- Class A solid state
- Broadband (instantaneous single band): 100 kHz – 200 MHz
- Typical output power : 500 W CW
- Linear output power (1 dB compression) guaranteed with harmonics <-20 dBc:
 - P1dB > 500 W and H < -20 dBc up to 100 MHz
 - P1dB > 200 W and H < -20 dBc from 100 MHz to 200 MHz
- Air cooling: self contained fans
- Can operate in full mismatch conditions without damage
- Reliable, efficient and robust
- 19" Rack
- 3 years standard warranty

Maintenance:

- Amplifier designed for minimal maintenance
 - ⇒ Easy access to all parts
 - ⇒ Modular design
 - ⇒ Repairs with minimum adjustments
- Rapid diagnostic
- Minimal downtime
- Contract for preventive and corrective maintenance available

Applications:

- EMC tests
- RF tests and instrumentation
- Radiocommunication
- Measurement and research laboratories

Versions:

- **GN 500 D** amplifier with:
 - ⇒ Display
 - ⇒ Digital control
 - ⇒ IEEE 488 GPIB Communication
- **GN 500 DC** : GN 500 D with :
 - ⇒ Integrated bidirectional coupler
 - ⇒ display of instantaneous power

GN series:

- GN 1000 => 1000 W CW
- GN 2000 => 2000 W CW
- GN 3500 => 3500 W CW
- GN 7000 => 7000 W CW
- GN 12000 => 12000 W CW

Prana additional options:

- External coupler
- Supply and integration inside a cabinet
- Bulk Current Injection + Calibration JIG
- RF Power cable
- Switching unit




Specifications

Frequency bandwidth	100 kHz - 200 MHz
Typical output power	500 W
Power at 3 dB compression	550 W min. up to 100 MHz / 280 W min. from 100 MHz to 200 MHz
Power at 1 dB compression	450 W min. up to 100 MHz / 180 W min. from 100 MHz to 200 MHz
Harmonics distortion	H2,H3 < -20 dBc for the output power at 1 dB compression limit
Class type	Class A
Gain	60 dB
Linear power gain flatness	± 3 dB max
Mismatch tolerance	infinite without damage
Input impedance	50 ohms / VSWR: 2:1max
Output impedance	50 ohms / VSWR: 2:1max
Input power	+10 dBm max.
RF input connector	Type N fem. (front or rear panel) – other connector type on request
RF output connector	Type N fem. (front or rear panel) – other connector type on request
Safety interlock	Connector type BNC
Digital control	Transistors, power supplies and internal temperature
Communication interface	IEEE 488, RS232
4 lines digital display	Status, faults, (direct and reverse instantaneous power for DC version)
Ambient operating temperature	0 °C / + 35 °C
Room temperature storage	-20 °C / +70 °C
Cooling	Forced air: 240 l/sec max. (self contained fans)
Power voltage	200-250 VAC, 47-63 Hz, single phase
Rated current	2 kVA
Dimensions	600 x 840 x 312 mm (7U) / 23.6 x 33.1 x 12.3 in (7U)
Weight	44 kg / 97 lb

GN 500 DC versions

Integrated bidirectional power coupler	Coupling factor 49 dB (DC version) ± 0.4 dB
Power coupling connector	Type N fem. (rear panel)
Estimated output power losses due to the coupler	0.3 dB



Electrical and Mechanical Specifications subject to change without notice.